

3/pt

- 1 -

Motor vehicle door lock system with speed unlocking

The invention relates to a motor vehicle door lock system with a motor vehicle lock which can be locked and unlocked by a motor and which can be opened mechanically or by a motor, and with control electronics with the features of the preamble of claim 1.

Conventional electromechanical motor vehicle door lock systems with radio remote control, but without the passive entry function, are known. In these classical vehicle door lock systems the operator presses a button on the remote control module. This activates the control electronics which passes through its reaction phase immediately. Based on the distance of the operator when the button of the remote control module is pressed, the operator reaches the outside door handle on the motor vehicle door with such a long time delay that the reaction phase of the control electronics has long been completed and the motor vehicle lock has been unlocked. By pulling on the outside door handle, the operator opens the motor vehicle door, the motor vehicle lock either opening mechanically, therefore the detent pawl being lifted by the motion of the outside door handle, or opening electromechanically or pneumatically, the outside door handle delivering a control signal to the opening drive to raise the detent pawl.

One such conventional electromechanical motor vehicle door lock system is known for example from US - A - 5,240,296. The lock element is driven by an electric motorized central interlock drive with an electric drive motor and a worm gear pair. The worm wheel of the worm gear pair is the drive element of the central interlock drive and it runs comparatively slowly. The shifting of the lock element from the locked position into the unlocked position by means of the central interlock drive requires at least 50 ms, usually longer.

Control electronics with a so-called passive entry function, also called an "electronic key", differs from the above explained classical motor vehicle door lock system in that on the

remote control module no manipulation is necessary, therefore a button need not be pressed to unlock the motor vehicle lock when approaching the motor vehicle. Rather, this takes place all by itself simply when the operator approaches the motor vehicle.

A motor vehicle door lock system with a passive entry function requires for the control electronics a certain reaction phase which is ordinarily composed of a starting interval to activate the system as the remote control module approaches, an authorization check interval to check the operator for his authorization using the coding of the signals exchanged between the remote control module and the control electronics, and finally the actual action interval in which the action takes place, especially the unlocking of the motor vehicle lock is carried out. (A corresponding reaction phase is also needed when locking the motor vehicle door lock system. But this is less critical because it is essentially unnoticed by the operator.)

A length of the reaction phase of roughly 150 milliseconds compared to conventional motor vehicle door lock systems is perceived as long if the starting interval is begun only when the outside door handle is activated. Pulling the outside door handle or the like can take place in a passive entry function under certain circumstances when the reaction phase of the control electronics has not yet been completed. The operator is annoyed that he must then pull the door handle a second time because this is interpreted as a "malfunction".

Since the resulting total time of the reaction phase cannot be shortened as much as desired, attempts have already been made to conceal the delay time (DE - A - 195 21 024). In this motor vehicle door lock system the starting interval and the authorization check interval of the control electronics are shifted into the phase which precedes the actual operation phase which is noticeable to the operator. Then, simply the remaining time which corresponds to the reaction time of mechanical, conventional motor vehicle door lock systems is noticeable to the operator.

A different approach is to have the starting interval of the control electronics initiated not only when the outside door handle is activated, but to use the approach of the hand of the operator to the outside door handle to initiate the starting interval. For this purpose, a

proximity sensor on the outside door handle is known (DE - A - 197 52 974; DE - A - 196 17 038), by which the proximity of the hand of the operator is acquired roughly 100 to 150 ml before the hand touches of the outside door handle. Initiation of the starting interval of the control electronics, therefore the "wakening" of the control electronics, therefore takes place so far in advance of the actually pulling of the outside door handle that the starting interval and generally also the authorization check interval have already been completed when the outside door handle is in fact moved by the hand of the operator.

The use of proximity sensors in motor vehicle door lock systems of the type under consideration entails various difficulties. On the one hand, the proximity sensors have a comparatively high rest current, on the other hand it is difficult to set a stable, definite response threshold. External influences such as rain, snow, dirt and dust greatly change the measured values in capacitive proximity sensors. Finally, in proximity sensors the problem of the stray electromagnetic radiation emitted by them cannot be ignored. Therefore, in spite of the aforementioned difficulties, motor vehicle door lock systems with the passive entry function in which only actuation of the outside door handle by the hand of the operator initiates the starting interval of the control electronics also have major advantages.

As can be taken from the aforementioned, in motor vehicle door lock systems with a passive entry function in all the aforementioned versions there is the problem that the reaction of the control electronics is preferably to be shortened as much as possible, in any case with respect to perception by the operator.

For themselves, it is known in motor vehicle door lock systems that the central interlock drive can be connected via a centrifugal clutch to the drive element for the lock element (EP 0 064 942 B1). This makes it possible to move the lock element by hand without major resistance if the central interlock drive is stationary. This is one alternative to the initially addressed construction of a conventional electromechanical motor vehicle door lock system in which this shifting by hand is implemented without major resistance by a corresponding configuration of the lock element. In any case the construction there does not

act in each position of the central interlock drive, therefore especially not when the central interlock drive remains stopped in an unintended position. Here the use of a centrifugal clutch has clear advantages.

In the motor vehicle door lock systems with a centrifugal clutch, on the central interlock drive the problem of reaction time then arises even if there is no passive entry function. The central interlock drive must first reach the necessary rpm before the centrifugal clutch engages and closes the energy transmission train to the lock mechanism.

The teaching of the invention is to improve a motor vehicle door lock system of the type under consideration, especially one with a passive entry function with respect to the reaction of the control electronics with consideration of the fact that the central interlock drive is equipped with a clutch which engages only with the beginning of minimum rpm, especially in the form of a centrifugal clutch.

The aforementioned object is achieved by a motor vehicle door lock system as claimed in the invention by the features of the characterizing part of claim 1. On the central interlock drive of each motor vehicle lock a clutch which engages only with the beginning of minimum rpm, especially in the form of a centrifugal clutch, is assigned to the motor vehicle door lock system. Then, additional speed unlocking is implemented in a manner which is tailored to the particulars of the centrifugal clutch. This is based on the finding that speed unlocking is achieved when the centrifugal clutch is essentially bypassed for the unlocking process. In principle, all the advantages of the use of a centrifugal clutch are achieved, nevertheless the disadvantage of the use of one such clutch is eliminated such that it needs a certain time until the central interlock drive, especially after the end of the authorization check interval in a passive entry function, starts and reaches the minimum rpm and only then is able to move the lock element via the centrifugal clutch.

As claimed in the invention, immediately after starting the central interlock drive in the passive entry function, therefore immediately after completion of the authorization check interval and in the first part of the action interval the lock element is moved into the unlocked

position. The corresponding applies of course to an element which is downstream of the lock element in the lock mechanism in the energy transmission chain. What is important is that by means of the speed unlocking element the unlocked position of the motor vehicle lock can be reached within a few milliseconds, especially roughly 10 ms. The effort necessary for this purpose is minimal, only a simple bypass construction for the clutch is necessary. The advantages of using a clutch, especially in the form of a centrifugal clutch, are preserved. Its disadvantages, specifically the delay of the response of the central interlock drive are however elegantly eliminated as claimed in the invention.

It is important that the central interlock drive itself is made classically with a slow running drive element and also the time delay for the response which is caused by the centrifugal clutch continues to be present. The central interlock drive is followed-up with an inevitable time delay and after a slightly longer time interval is then in its readiness position for the next function.

The teaching of the invention can be used especially valuably when as already explained above for the prior art, the starting interval is initiated by the hand of the operator in fact actuating, especially touching the outside door handle. In this form which can dispense with a proximity sensor, for a long time the length of the reaction phase was a special problem because the time advance which is an advantage in proximity sensors is absent. But also in a motor vehicle door lock system equipped with a proximity sensor does the teaching of the invention of course yield a time advantage.

The teaching of the invention can be integrated especially feasibly also in the already existing classical electromechanical motor vehicle door lock systems without major additional cost so that in existing constructions the passive entry function can be used without disadvantages in the ease of actuation.

The teaching of this invention can be used especially when the motor vehicle door lock is made as an electric lock which is actuated by sensors in the lock mechanism. In one such technology the chains of dynamic effect from the outside door handle, the inside door

handle, and optionally from the lock cylinder into the lock mechanism are used only for actuation of the corresponding switches or to influence the corresponding sensors. Based on the existence of mechanical chains of dynamic effect however, if necessary the lock mechanism can be used for purposes of actuating the detent pawl, etc. This concept is the subject matter of the older patent application 199 24 447 of the applicant.

Finally, the teaching of this invention can also be used in a motor vehicle door lock system without a passive entry function, for example in especially comfortable motor vehicle door lock systems in conjunction with the actuation of the outside door handle.

Preferred embodiments and developments of the teaching of the invention are the subject matter of the dependent claims. The subject matter of the invention is otherwise also a motor vehicle lock as such, as can be used in a manner individualized to the function of the invention in a motor vehicle door lock system of the type under consideration.

The invention is detailed below using drawings which show only one embodiment.

Figure 1 shows in a schematic and perspective view a motor vehicle with a door lock system of the type under consideration,

Figure 2 shows an outside door handle arrangement in a motor vehicle door lock system as shown in Figure 1,

Figure 3 shows in a schematic a motor vehicle lock with a central interlock drive and speed unlocking element according to one embodiment of the invention.

The motor vehicle 1 which is shown schematically in Figure 1 has a motor vehicle door lock system in which the different motor vehicle locks 2 for motor vehicle doors and motor vehicle hatches are shown schematically with their installation positions. Each motor vehicle lock 2 can be locked and unlocked by a motor, preferably an electric motor, likewise by means of a central interlock drive. In the version as an electric lock, as shown here, the motor vehicle lock 2 additionally has the possibility of motorized opening, therefore lifting of the detent pawl, by means of an opening drive. In this case unlocking and locking can also take place using only circuitry. Another version is also to equip the motor vehicle locks 2

with a auxiliary closing drive which can be identical to the opening drive or can be separate from it. Reference should be made in this respect in general to the prior art (DE - A - 196 29 709, etc.).

In the motor vehicle door lock system there is control electronics 3 which is illustrated here as central control electronics, which however can also be assigned decentralized to each of the motor vehicle locks 2. There are furthermore a key-operated hood lock 4 for the hood of the motor vehicle and a remote control module 5 which is made as a passive chip card. The control electronics 3 works overall with a passive entry function, therefore with an "electronic key". Also in this respect reference should be made to the aforementioned prior art. It is important that fundamentally the teaching can also be used in a motor vehicle door lock system with control electronics which is not equipped with a passive entry function.

On the motor vehicle body an outside door handle 6 or the like is recognizable on the respective motor vehicle door, and on the driver's door a lock cylinder 7 for actuation with a mechanical key 8, this actuation taking place in the case of an emergency (emergency unlocking and optionally emergency opening).

As has already been explained for the prior art which forms the starting point (DE - A - 195 21 024), in this motor vehicle door lock system it must be considered that the control electronics 3 in terms of time requires a reaction phase with a starting interval, authorization check interval and action interval, especially for unlocking the motor vehicle lock 2.

It has already been established in the prior art that the starting interval of the control electronics 3 is initiated by the hand of the operator touching the outside door handle 6. Figure 2 shows a typical door handle arrangement of a motor vehicle door lock system of the type under consideration with the outside door handle 6 and the lock cylinder 7. A switching means 9 on the outside door handle 6 with which the operating signal is triggered when the outside door handle 6 is pulled in order to trigger the electric opening drive for lifting the detent pawl is also shown. This is one version of an electric lock; in a mechanically activated lock the switching means 9 is replaced by a transmission mechanism.

Figure 3 shows that the motor vehicle lock 2 of the motor vehicle door lock system in this embodiment has first a lock element 10 which can be shifted between a locked position and an unlocked position. As Figure 3 shows, the lock element 10 is coupled to the remaining lock mechanism 11, and this lock mechanism 11 need not be further explained. The lock element 10 in any case is overthrown by means of a preferably electrical central interlock drive 12 which is shown here with a slow-running drive element 13 from the locked position into the unlocked position and vice versa. This is indicated by the letters VS [locked position] and ES [unlocked position] on the lock mechanism 11.

In the locked position the motor vehicle lock 2 cannot be opened, in the unlocked position of the lock element 10 the motor vehicle lock 2 can be opened. How opening proceeds, whether mechanically or by motor, is irrelevant in this connection. To this extent the alternatives of the prior art can be accomplished here.

The embodiment shown illustrates the electrical central interlock drive 12 with an electrical drive motor and a worm gear pair with a worm gear which forms the slow-running drive element 13 for the lock element 10. Alternatives to the corresponding central interlock drives 12 are also linear drives with a threaded spindle as the slow-running drive element 13. Pneumatic central interlock drives 12 are also of course known.

It is important that slow-running drive element 13 can move the lock element 10 back and forth between the locked position and the unlocked position, but that this takes place relatively slowly.

It is now provided as claimed in the invention that between the central interlock drive 12 and the drive element 13 there is a clutch 14 which engages only with the beginning of a minimum rpm and which ensures that the lock element 10 can be easily moved by hand with the central interlock drive 12 stationary. Generally, this clutch 14 is a centrifugal clutch in one or the other embodiment. Reference should be made to the prior art in this respect (EP 0 064 942 B1).

The fact that the clutch 14 engages only with the beginning of minimum rpm of the

central interlock drive 12 means that after the authorization check interval a longer time passes again until the unlocked position of the lock mechanism is reached from the locked position. This is answered by the fact that the speed unlocking element 15 is assigned to the central interlock drive 12 on this side of the clutch 14. The speed unlocking element can be immediately actuated by the central interlock drive 12 upon starting. When the central interlock drive 12 starts, immediately after the control electronics 3 has completed the authorization check interval, the speed unlocking element 15 is also immediately actuated. It is now configured such that it immediately moves the lock element 10 or an element of the lock mechanism 11 downstream of the lock element out of the locked position into the unlocked position.

The central interlock drive 12 itself runs, with the clutch 14 engaged, accordingly more slowly into the unlocked position or via the unlocked position into the next rest position. The advantage of bypassing the centrifugal clutch as necessary by the speed unlocking element 15 is accomplished advantageously when the control electronics 3 is not equipped for a passive entry function, especially when the outside door handle is actuated.

As has already been explained in the general part of the specification, the length of the reaction phase when the motor vehicle lock is unlocked is more problematic than when locking the motor vehicle lock, because it is essentially unnoticed by the operator there. The speed unlocking element 15 is therefore used first of all for unlocking and thus for moving the lock element 10 out of the locked position into the unlocked position.

After completion of the reaction time which is typical of the central interlock drive 12 including the clutch 14, the lock mechanism 11 is again completely synchronous. The central interlock drive 12 with its drive element 13 can then be used in the classical manner for locking of the motor vehicle lock 2, therefore for return of the control element 10 from the unlocked position into the locked position.

Otherwise, it can be intended for the central interlock drive 12 to provide for unlocking, therefore for displacement of the lock element 10 out of the locked position into

the unlocked position, in motor vehicle locks 2 on a motor vehicle which have not been directly actuated by the operator, therefore for example on the passenger's door and on the two rear side doors.

With respect to the configuration of the lock mechanism 11, it is recommended that the speed unlocking element 15 can be moved by the starting central interlock drive 12 out of its rest position into its actuation position and by the lock element 10 which has been reset from the unlocked position into the locked position or the element of the lock mechanism downstream of the lock element out of its actuation position back into its rest position.

The corresponding characteristics of the lock mechanism 11 can be accomplished by a backlash connection for which there are numerous models in the prior art. In this embodiment there is one version for this which is characterized in that the lock element 10 is entrained on one side by interlocking by the drive element 13 and in the opposite direction via releasable catching. As shown in Figure 3 an interlock element 13a is recognizable on the drive element 13. The releasable catching is not shown in Figure 3 for reasons of graphics.

The speed unlocking element 15 can be connected more or less by interlocking to the lock mechanism 11 or the lock element 10. But especially quick-reaction speed unlocking occurs by the speed unlocking element 15 being made as a spring snap element which is only released by the central interlock drive 12 and then snaps into its actuation position under spring force. The speed unlocking element 15 is triggered in the manner of a spring-loaded catch only by the starting central interlock drive 12, further motion of the lock element 10 into the unlocked position is then executed lighting-fast by the pretensioned spring.

The teaching of the invention is of special importance when for example there is no possibility for concealing part of the reaction time of the control electronics 3 by a proximity sensor. This therefore also applies to a motor vehicle door lock system in which the starting interval is initiated by the hand of the operator actuating the outside door handle 6, especially simply touching it.

The subject matter of the invention is not only a motor vehicle door lock system

overall, but also a motor vehicle lock individualized functionally to the invention, which, specifically assigned not only to the preferably electrical central interlock drive 12 with the slow running drive element 13, but also to the lock element 10, has the above explained clutch 14 with the speed unlocking element 15.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
22